

# C-Power Lubrication System

Proper lubrication is critical to bearing and machine performance. To help prevent premature failures, C-Power multi-point lubricators deliver grease to up to six lubrication points. C-Power multi-point lubricators are centralized lubrication systems that can be filled with Timken-formulated lubricants or many other types of commercial lubricants. Oil is not an option in this unit. A full line of accessories – including brackets, clamps, brushes, fittings and hose extensions – ease installation and offer a host of mounting options for hard-to-reach locations.

With more than a century of leadership in developing friction management solutions, Timken is a trusted source for a broad range of bearings – and products that help keep all bearings and related components running smoothly. Turn to Timken and C-Power multi-point lubricators to help reduce friction in your industrial applications.

## Timken C-Power Features:

- *Timken C-Power replaces the need for up to six single-point lubricators with one, easy to maintain multi-point system.*
- *Remote mounting addresses 'space confined lubrication points' with no pressure loss up to 16 feet per point.*
- *Versatile programmability from one to 24 months.*
- *Full pressure is maintained regardless of the number of lubrication points selected.*
- *Includes a complete kit of accessories, full instructions and enough pre-filled grease lines for six lubrication points.*

# TIMKEN

Where You Turn





**(MULTI-POINT  
LUBRICATOR)**



<b>Model Number</b>	250	500
<b>Name</b>	250 cc	500 cc
<b>Description</b>	Programmable multi-point lubricator capable of lubricating up to six points. The lubricant cartridge is replaceable.	Programmable multi-point lubricator capable of lubricating up to six points. The lubricant cartridge is replaceable.
<b>Complete Unit</b> <small>(XXX is the lubricant reference)</small>	PC322XXX	PC352XXX
<b>Lubrication Cartridge Part Number</b> <small>(XXX is the lubricant reference)</small>	<b>Replacement set (includes battery and lubricant cartridge):</b> 8.45 fl. oz. (250 cm <sup>3</sup> ) unit: PC321XXX	<b>Replacement set (includes battery and lubricant cartridge):</b> 16.9 fl. oz. (500 cm <sup>3</sup> ) unit: PC351XXX
<b>Lubrication Period</b>	Variable according to set-up; 1 day to 24 months (battery limited)	Variable according to set-up; 1 day to 24 months (battery limited)
<b>Max. Pressure</b>	360 psi/25 bar	360 psi/25 bar
<b>Application Temperature</b>	-4° F to 140° F (-20° C to 60° C)	-4° F to 140° F (-20° C to 60° C)
<b>Approx. Weight</b>	3.4 lb (1.53kg)	4.0 lb (1.82kg)
<b>Dimensions</b>	Height: 14.3" (360 mm) Max. diameter: 3.6" (92 mm)	Height: 15.8" (400 mm) Max. diameter: 3.6" (92 mm)

**TIMKEN**  
Where You Turn

**Bearings • Specialty Steel • Precision Components • Lubrication • Seals • Remanufacture and Repair • Engineering Services**

[www.timken.com](http://www.timken.com)

Timken® is a registered trademark of The Timken Company

Copyright 2006 The Timken Company  
Printed in U.S.A.  
000 00-00-00 Order No. 0000